

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: 1-800-633-8253

Page 1

PRODUCT CODE: 8M6681

PRODUCT NAME: 8-M-6681 DK BLUE GRAY ENAMEL

PRODUCT CODE: 8M6681

HMS CODES: H C F R P
1 3 0 J

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: P.F.I. , INC. - PAINTS FOR INDUSTRY

ADDRESS : 9215 SANTA FE SPRINGS RD.
SANTA FE SPRINGS, CA, 90670

INFORMATION PHONE : (562) 946-6666

DATE PRINTED : 6/4/2009

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS

CAS NUMBER VAPOR PRESSURE @TEMP (F) WEIGHT PERCENT

MINERAL SPIRIT 8052-41-3 2 68 19
ACETONE 67-64-1 185 68 3
METHYL ETHYL KETONE 78-93-3 70 68 2

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.***

IN ACCORDANCE WITH THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986(SARA) THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 133.0 deg F TO 315.0 deg F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: 333 Gms/Lit
COATING V.O.C.: 2.7 Lbs/Gal
SOLUBILITY IN WATER: SOLUBILITY BP
APPEARANCE AND ODOR: APPEARANCE BP

SPECIFIC GRAVITY (H2O=1): 1.0805
EVAPORATION RATE: SLOWER THAN ETHER
MATERIAL V.O.C.: 317 Gms/Lit
MATERIAL V.O.C.: 2.6 Lbs/Gal

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -4.00 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0 UPPER: 12.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

Water may be ineffective on fire but water spray may be used to cool closed containers exposed to extreme heat or fire to prevent pressure build up.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep away from heat, sparks and open flame. Closed containers may explode when exposed to extreme heat or fire. Do not apply to hot surfaces.