



Get the most comprehensive  
MSDS/HazCom program on the market!

## Material Safety Data Sheet

---

SECTION I - Material Identity  
 SECTION II - Manufacturer's Information  
 SECTION III - Physical/Chemical Characteristics  
 SECTION IV - Fire and Explosion Hazard Data  
 SECTION V - Reactivity Data  
 SECTION VI - Health Hazard Data  
 SECTION VII - Precautions for Safe Handling and Use  
 SECTION VIII - Control Measures  
 SECTION IX - Label Data  
 SECTION X - Transportation Data  
 SECTION XI - Site Specific/Reporting Information  
 SECTION XII - Ingredients/Identity Information

---

### SECTION I - Material Identity

---

Item Name	
Part Number/Trade Name	LUBRIPLATE NO. 630-AA, 630-A, 630-2, 630-AA-W, 630-AAA
National Stock Number	9150011098726
CAGE Code	<u>73219</u>
Part Number Indicator	B
MSDS Number	185224
HAZ Code	B

### SECTION II - Manufacturer's Information

---

Manufacturer Name	FISKE BROS REFINING CO
Street	129 LOCKWOOD ST
City	NEWARK
State	NJ
Country	US
Zip Code	07105-4720
Emergency Phone	201-589-9150
Information Phone	201-589-9150

### MSDS Preparer's Information

---

MSDS Preparer Name	ROBERT J. SIBILIA
Date MSDS Prepared/Revised	01MAY87
Date of Technical Review	12JAN94
Active Indicator	Y
Item Manager	75

### Alternate Vendors

---

Vendor #5 CAGE	BSFSB
----------------	-------

---

### SECTION III - Physical/Chemical Characteristics

---

Specification Number	N/R
Specification Type/Grade/Class	N/R
Hazard Storage Compatibility Code	N1
NRC License Number	N/R
Net Propellant Weight (Ammo)	N/R
Appearance/Odor	SMOOTH, TAN GREASE WITH MINERAL OIL ODOR
Boiling Point	>550F, >288C
Melting Point	SEMI-SOLID
Vapor Pressure	<0.01
Vapor Density	>5
Specific Gravity	0.95
Decomposition Temperature	N/R
Evaporation Rate	<0.01 (BUTYL ACETATE=1)
Solubility in Water	NEGLIGIBLE
Percent Volatiles by Volume	N/K
Chemical pH	N/R
Corrosion Rate	N/R
Container Pressure Code	4
Temperature Code	8
Product State Code	U

---

### SECTION IV - Fire and Explosion Hazard Data

---

Flash Point	400
Flash Point Method	COC
Lower Explosion Limit	0.9
Upper Explosion Limit	7.0
Extinguishing Media	FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG)
Special Fire Fighting Procedures	COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES
Unusual Fire/Explosion Hazards	DO NOT STORE OR MIX WITH

STRONG OXIDANTS. EMPTY  
CONTAINERS RETAIN RESIDUE. DO  
NOT CUT, DRILL, GRIND, OR  
WELD, AS THEY MAY EXPLODE

---

### SECTION V - Reactivity Data

---

Stability	YES
Stability Conditions to Avoid	N/A
Materials to Avoid	AVOID CONTACT WITH STRONG OXIDANTS LIKE LIQUID CHLORINE, CONCENTRATED OXYGEN
Hazardous Decomposition Products	MAY FORM SULFUR DIOXIDE. IF INCOMPLETE COMBUSTION, CARBON MONOXIDE
Hazardous Polymerization	NO
Polymerization Conditions to Avoid	N/A
LD50 - LD50 Mixture	TLV: 5 MG/M3 OIL MIST

---

### SECTION VI - Health Hazard Data

---

Route of Entry: Skin	YES
Route of Entry: Ingestion	YES
Route of Entry: Inhalation	YES
Health Hazards - Acute and Chronic	PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTEAMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVEREPULMONARY INJURY
Carcinogenity: NTP	NO
Carcinogenity: IARC	NO
Carcinogenity: OSHA	NO
Explanation of Carcinogenity	NOT CARCINOGENIC
Symptoms of Overexposure	HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. ASA PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED
Medical Cond. Aggrevated by Exposure	NONE SPECIFIED BY MANUFACTURER
Emergency/First Aid Procedures	EYE-FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN. SKIN-REMOVE CONTAMINATED CLOTHING & WASH WITH SOAP &

WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, CONTACT PHYSICIAN IMMEDIATELY. INHALATION-IF OVERCOME BY VAPOR FROM HOT PRODUCT, REMOVE FROM EXPOSURE & CALL PHYSICIAN. INGESTION-CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING

---

## SECTION VII - Precautions for Safe Handling and Use

---

Steps if Material Released/Spilled	SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCT OUT OF SEWERS & WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS & WATER COURSES
Neutralizing Agent	N/R
Waste Disposal Method	ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE DISPOSAL FACILITY OR SITE
Handling and Storage Precautions	KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS
Other Precautions	REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT

---

## SECTION VIII - Control Measures

---

Respiratory Protection	NORMALLY NOT NEEDED
Ventilation	LOCAL EXHAUST-USE TO CAPTURE FUMES AND VAPORS
Protective Gloves	USE OIL-RESISTANT GLOVES, IF NEEDED
Eye Protection	IF CHANCE OF EYE CONTACT, WEAR GOGGLES
Other Protective Equipment	USE OIL-RESISTANT APRON, IF NEEDED
Work Hygenic Practices	LAUNDRER CLOTHING BEFORE REUSE
Supplemental Health/Safety Data	NONE

---

## SECTION IX - Label Data

---

Protect Eye	YES
Protect Skin	YES
Protect Respiratory	NO
Chronic Indicator	UNKNOWN
Contact Code	SLIGHT
Fire Code	UNKNOWN
Health Code	UNKNOWN
React Code	UNKNOWN

---

**SECTION X - Transportation Data**

---

Container Quantity	14
Unit of Measure	OZF

---

**SECTION XI - Site Specific/Reporting Information**

---

Volatile Organic Compounds (P/G)	0
Volatile Organic Compounds (G/L)	0

---

**SECTION XII - Ingredients/Identity Information**

---

Ingredient #	1
Ingredient Name	NON HAZARDOUS INGREDIENT
Proprietary	NO
Percent	0
OSHA PEL	NOT ESTABLISHED
ACGIH TLV	NOT ESTABLISHED

---