

# MATERIAL SAFETY DATA SHEET

# PRODUCT IDENTIFICATION

MANUFACTURER'S NAME PENNZOIL COMPANY

ADDRESS

P.O. BOX 2967

HOUSTON, TX 77252-2967

EMERGENCY TELEPHONE NO. (800) 546-6040

CAS NUMBER: MIXTURE

MSDS CODE:

013703

NFPA HAZARD IDENTIFICATION

DEGREE OF HAZARD

HAZARD RATINGS

HEALTH: 1

0-LEAST

FIRE: 1

1-SLIGHT

2-MODERATE

REACTIVITY: 0

3-HIGH

4-EXTREME

TRADE NAME: PENNLITH≈ SHD EP GREASE - ALL GRADES

EP 220 #2, EP 460 #1.1/2, EP 1500 #1

BY: ENVIRONMENTAL, SAFETY & HEALTH

(800) 546-6227

EFFECTIVE DATE: MAY 08, 1998

SUPERSEDES DATE: ORIGINAL VERSION

### INGREDIENTS

COMPONENT NAME AS NUMBER	HAZARDOU IN BLEND	3 PERCENTAGE MIN MAX			COMPONENT EXPOSURE LIMIT		UNIT
SYNTHETIC LUBRICANT TRADE SECRET	N0	55	TO	. 85	OSHA PEL ACGIH TLV		LIMIT LIMIT
LITHIUM SOAP MIXTURE	NO	5	ТО	15	OSHA PEL ACGIH TLV	NO	LIMIT
MIXTURE	NO	10	T0	30	OSHA PEL ACGIH TLV		LIMIT LIMIT
ANTIWEAR AGENT MIXTURE	, NO	·	<	.5	OSHA PEL ACGIH TLV		LIMIT LIMIT
DYE MIXTURE	NO		<b>&lt;</b>	_ 1	OSHA PEL ACGIH TLV		LIMIT LIMIT

# 3. HEALTH INFORMATION AND PROTECTION

CODE: 013703 NAME: PENNLITH≈ SHD EP GREASE - ALL GRADES

PAGE 02

EYE CONTACT:

THIS PRODUCT IS MINIMALLY IRRITATING TO THE EYES UPON DIRECT CONTACT. BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS.

JKIN CONTACT:

AVOID SKIN CONTACT. THIS PRODUCT IS MINIMALLY IRRITATING TO THE SKIN UPON DIRECT CONTACT. PROLONGED OR REPEATED CONTACT MAY RESULT IN CONTACT DERMATITIS WHICH IS CHARACTERIZED BY DRYNESS, CHAPPING, AND REDDENING. THIS CONDITION MAY MAKE THE SKIN MORE SUSCEPTIBLE TO OTHER IRRITANTS, SENSITIZERS, AND DISEASE. PROLONGED OR REPEATED CONTACT MAY RESULT IN OIL ACNE WHICH IS CHARACTERIZED BY BLACKHEADS WITH POSSIBLE SECONDARY INFECTION.

INHALATION:

THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITIONS. CAUTION SHOULD BE TAKEN TO PREVENT AEROSOLIZATION OR MISTING OF THIS PRODUCT. THE PERMISSABLE EXPOSURE LIMIT (PEL) AND THRESHOLD LIMIT VALUE (TLV) FOR THIS PRODUCT AS OIL MIST IS 5 MG/M3. EXPOSURES BELOW 5 MG/M3 APPEAR TO BE WITHOUT SIGNIFICANT HEALTH RISK. THE SHORT-TERM EXPOSURE LIMIT FOR THIS PRODUCT AS AN OIL MIST IS 10 MG/M3. SEE HEALTH DATA SECTION BELOW.

INGESTION:

DO NOT INGEST. THIS PRODUCT IS RELATIVELY NON-TOXIC BY INGESTION. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA. SEE HEALTH DATA SECTION BELOW.

HEALTH DATA:

GREASES CONSIST OF SOLID OR SEMISOLID DISPERSIONS OF METALLIC SOAPS AND OTHER THICKENERS IN A MINERAL OIL BASE. LONG-TERM EXPOSURE TO SMALL DOSES OF MINERAL OIL BY INHALATION, ASPIRATION OR INGESTION LEADING TO ASPIRATION CAN LEAD TO LIPID PNUEMONIA OR LIPID GRANULOMA OF THE LUNG. THESE ARE LOW-GRADE, CHRONIC, LOCALIZED TISSUE REACTIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CONCLUDED THAT THE DATA ARE INADEQUATE TO EVALUATE THE CARCINOGENICITY OF FORMULATED PRODUCTS TO EXPERIMENTAL ANIMALS (1984). THIS PRODUCT IS NOT CARCINOGENIC

ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

#### 4. EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER AND CONTINUE FLUSHING UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM TO HOSPITAL IMMEDIATELY.

SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED AREA THOROUGHLY WITH SOAP AND WATER. IF REDNESS OR IRRITATION OCCURS, SEEK MEDICAL ATTENTION. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERELY BURNED, REMOVE TO A HOSPITAL IMMEDIATELY. IF INJECTED UNDER SKIN, CONTACT A PHYSICIAN IMMEDIATELY. HIGH PRESSURE GREASE GUN INJECTION INJURY, CAN CAUSE SERIOUS, DELAYED SOFT TISSUE INJURY. DELAY IN TREATMENT MAY CAUSE LOSS OF AFFECTED PART OF THE BODY.

INHALATION:

THIS MATERIAL HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION EXPOSURE AT AMBIENT CONDITIONS. IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, REMOVE VICTIM FROM EXPOSURE.

INGESTION:

DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

# 5. PERSONAL HEALTH PROTECTION INFORMATION

CODE: 013703 NAME: PENNLITH≈ SHD EP GREASE - ALL GRADES

PAGE 03

EYE PROTECTION:

EYE PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF MATERIAL IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES, WEAR PLASTIC FACE SHIELD OR SPLASH-PROOF SAFETY GOGGLES.

SKIN PROTECTION: NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES. FOR PROLONGED OR REPEATED EXPOSURES, USE IMPERVIOUS CLOTHING (BOOTS, GLOVES, APRONS, ETC.) OVER PARTS OF THE BODY SUBJECT TO EXPOSURE. IF HANDLING HOT MATERIAL, USE INSULATED PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ETC.). LAUNDER SOILED CLOTHES. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES, WHICH CANNOT BE DECONTAMINATED.

RESPIRATORY PROTECTION: RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, USE AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. ALL RESPIRATORS MUST BE NIOSH CERTIFIED. DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.

**VENTILATION:** 

IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE SPECIFIED EXPOSURE OR FLAMMABLE LIMITS.

OTHER:

CONSUMPTION OF FOOD AND BEVERAGE SHOULD BE AVOIDED IN WORK AREAS WHERE HYDROCARBONS ARE PRESENT. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING.

### FIRE PROTECTION INFORMATION

LASH POINT: 485 F

TEST METHOD: ASTM D-92

AUTOIGNITION TEMPERATURE: 500 F

TEST METHOD: NO DATA

FLAMMABLE LIMITS IN AIR % BY VOLUME

LOWER: NO DATA

UPPER: NO DATA

EXTINGUISHING

MEDIA:

USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT. BURNING LIQUID.

UNUSUAL FIRE AND EXPLOSIVE CONDITIONS:

DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

### 7. REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.): STABLE

CONDITIONS TO AVOID: NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

INCOMPATIBILITY MATERIALS TO AVOID: MAY REACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

#### 8. ENVIRONMENTAL PRECAUTIONS

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: CONSULT HEALTH EFFECT INFORMATION IN SECTION III, PERSONAL HEALTH PROTECTION INFORMATION IN SECTION V, FIRE PROTECTION INFORMATION IN SECTION VI, AND REACTIVITY DATA IN SECTION VII. NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.

ASTE DISPOSAL METHOD:

ALL DISPOSALS MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS. THE MATERIAL, IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO STATE AND LOCAL REGULATIONS. CAUTION: IF REGULATED SOLVENTS ARE USED TO CLEAN UP SPILLED MATERIAL, THE RESULTING WASTE MIXTURE MAY BE REGULATED. DEPARTMENT OF TRANSPORTATION (DOT) REGULATIONS MAY APPLY FOR TRANSPORTING THIS MATERIAL WHEN SPILLED. WASTE MATERIAL MAY BE LANDFILLED OR INCINERATED AT AN APPROVED FACILITY. MATERIALS SHOULD BE RECYCLED IF POSSIBLE.

### 9. MISCELLANEOUS

HANDLING AND STORAGE REQUIREMENTS: DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106--FLAMMABLE AND COMBUSTIBLE LIQUIDS.

ADDITIONAL INFORMATION:

THIS MIXTURE MAY BE FORMULATED IN PART WITH COMPONENTS PURCHASED FROM OTHER COMPANIES. IN MANY INSTANCES, ESPECIALLY WHEN PROPRIETARY OR TRADE SECRET MATERIALS ARE USED, PENNZOIL COMPANY MUST RELY UPON THE HAZARD EVALUATION OF SUCH COMPONENTS SUBMITTED TO PENNZOIL BY THAT PRODUCT'S MANUFACTURER OR IMPORTER.

THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS AT OR GREATER THAN 1.0% (0.1% FOR CARCINOGENS).

ALL INGREDIENTS OF THIS PRODUCT IS LISTED ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY.

CODE: 013703 NAME: PENNLITH≈ SHD EP GREASE - ALL GRADES

DOT: NOT REGULATED.

# 10. PHYSICAL PROPERTIES

BOILING POINT: NO DATA MELTING POINT: 545 F

PERCENT VOLATILE: NO DATA

VAPOR DENSITY

(AIR=1): NO DATA

APPEARANCE:

RED SEMI-SOLID

**EVAPORATION RATE** 

(EE=1): NO DATA

ODOR:

BLAND

SPECIFIC GRAVITY: 0.85

VAPOR PRESSURE: NO DATA

MOLECULAR WEIGHT: NO DATA

SOLUBILITY:

NEGLIGIBLE

#### DISCLAIMER OF WARRANTY:

THE INFORMATION CONTAINED HEREIN IS BASED UPON DATA AVAILABLE TO US, AND REFLECTS OUR BEST PROFESSIONAL JUDGEMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.