

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT**



MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT

SYNONYMS: Parts Washer Solvent; Petroleum Distillates; Petroleum Naptha;
Naptha, Solvent; Stoddard Solvent; Mineral Spirits.

**PRODUCT PART
NUMBERS:** 6605, 6638.

PRODUCT USE: Cleaning and degreasing metal parts.
If these products are used in combination with other products, refer to
the Material Safety Data Sheets for those products.

	24-HOUR EMERGENCY PHONE NUMBERS	
These numbers are for emergency use only. If you desire non-emergency product information, please call a phone number listed below.	MEDICAL:	TRANSPORTATION (SPILL):
	1-800-752-7869	1-800-468-1760

SUPPLIER: Safety-Kleen Corp.
5400 Legacy Drive
Cluster II, Building 3
Plano, Texas 75024
USA
1-800-669-5740

TECHNICAL INFORMATION: 1-800-669-5740, Press 1 then Extension 7500

MSDS FORM NUMBER: 82658 (Also formerly known as 82529) **ISSUE:** December 12, 2002

ORIGINAL ISSUE: January 26, 1995 (Also formerly January 7, 1993) **SUPERSEDES:** March 24, 2000

PREPARED BY: Product MSDS Coordinator **APPROVED BY:** MSDS Task Force

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

WT%	NAME	SYNONYM	CAS NO.	OSHA PEL		ACGIH TLV®		LD ^a	LC ^b
				TWA	STEL	TWA	STEL		
100	Distillates (petroleum), hydrotreated light ^e	N.Av.	64742-47-8	500 ^d ppm	N.Av.	100 ^d ppm	N.Av.	>5000 ^c	>5500 ^d mg/m ³ /4 hours

N.Av. = Not Available

^aOral-Rat LD (mg/kg)

^bInhalation-Rat LC

^cBased on Stoddard solvent: Skin-Rabbit
LD₅₀ >3000 mg/kg

^dBased on Stoddard Solvent.

^eBased on Stoddard Solvent, NIOSH IDLH
(Immediately Dangerous to Life or Health):
20000 mg/m³ (5000 ppm)

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Liquid, clear, colorless to pale yellow, mild hydrocarbon odor.

WARNING!

PHYSICAL HAZARD

Combustible liquid and vapor.

HEALTH HAZARDS

May be harmful if inhaled.

May irritate eyes and skin.

May be harmful if swallowed.

Contains material which may cause central nervous system damage.

ENVIRONMENTAL HAZARDS

Not toxic to aquatic life.

POTENTIAL HEALTH EFFECTS

INHALATION (BREATHING): High concentrations of vapor or mist may be harmful if inhaled. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

EYES: May cause irritation with watering, stinging, and/or redness.

SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful amounts.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

INGESTION (SWALLOWING): May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and central nervous system effects as noted under **INHALATION (BREATHING)**. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause toxic effects as noted under **INHALATION (BREATHING)**. Prolonged or repeated inhalation and/or ingestion has been suggested to produce kidney toxicity in dogs but in no other species, including humans. According to one unsubstantiated human case report, prolonged or repeated inhalation, skin contact, and/or ingestion may cause mild, acute chemical hepatitis and acute, yellow atrophy (size reduction) of the liver. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis); and/or burns.

CANCER INFORMATION: No known carcinogenicity. For more information, see **SECTION 11: CARCINOGENICITY**.

Also see **SECTION 15: CALIFORNIA**.

POTENTIAL ENVIRONMENTAL EFFECTS

Product is not toxic to aquatic life. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

SECTION 4: FIRST AID MEASURES

INHALATION (BREATHING): Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

EYES: If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

**INGESTION:
(SWALLOWING)** Do NOT induce vomiting. Immediately get medical attention. Call 1-800-752-7869 for additional information.
If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by mouth.

**NOTE TO
PHYSICIANS:** Treat symptomatically and supportively. Administration of gastric lavage, if warranted, should be performed by qualified medical personnel. Treatment may vary with condition of victim and specifics of incident. Call 1-800-752-7869 for additional information.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 148°F (64°C) (approximately) Tag Closed Cup

FLAMMABLE LIMITS IN AIR: **LOWER:** 0.7 VOL% (minimum)
UPPER: 5 VOL% (maximum)


**AUTOIGNITION
TEMPERATURE:** 410°F (210°C) (minimum)

**HAZARDOUS COMBUSTION
PRODUCTS:** Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

**CONDITIONS OF
FLAMMABILITY:** Heat, sparks, or flame.

EXTINGUISHING MEDIA: Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

**NFPA 704
HAZARD
IDENTIFICATION:** This information is intended solely for the use by individuals trained in this system.



**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

**FIRE FIGHTING
INSTRUCTIONS:**

Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

**FIRE AND
EXPLOSION HAZARDS:**

Vapor explosion hazard indoors, outdoors, or in sewers. Vapors may travel to ignition source and flashback. Vapors will spread along the ground and collect in low or confined areas. Run-off to sewer may create a fire hazard. Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface waters and sewers. Contain spill as a liquid for possible recovery or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING:

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using these products.

**SHIPPING AND
STORING:**

Keep container tightly closed when not in use and during transport. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORT INFORMATION** for Packing Group information.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Use NIOSH-certified, air-purifying respirators with organic vapor cartridges respiratory protective equipment when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air-purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

EYE PROTECTION: Where eye contact is likely, wear chemical goggles; contact lens use is not recommended.

SKIN PROTECTION: Where skin contact is likely, wear nitrile, supported neoprene, Viton®, polyvinyl alcohol (PVA), laminate (such as North Silver Shield®, Safety 4 4h®, Ansell Edmont Barrier®), or equivalent protective gloves; use of polyvinyl chloride (PVC), natural rubber (latex), or equivalent gloves is not recommended.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

PERSONAL HYGIENE: Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with the product.

OTHER PROTECTIVE EQUIPMENT: Where spills and splashes are likely, facilities storing or using this product should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, APPEARANCE, AND ODOR:	Liquid, clear, colorless to pale yellow, mild hydrocarbon odor.
ODOR THRESHOLD:	30 ppm (based on Stoddard Solvent)
MOLECULAR WEIGHT:	Not available.
SPECIFIC GRAVITY:	0.78 to 0.82 at 60°F/60°F (15.6°C/15.6°C) (water = 1)
DENSITY:	6.5 to 6.8 LB/US gal (780 to 820 g/l)
VAPOR DENSITY:	5 (air = 1) (approximately)
VAPOR PRESSURE:	0.2 mm Hg at 68°F (20°C) (approximately) 0.6 mm Hg at 100°F (38°C) (approximately)
BOILING POINT:	350°F (177°C) (initial)
FREEZING/MELTING POINT:	-45°F (-43°C) (maximum)
pH:	Not applicable.
EVAPORATION RATE:	0.1 (butyl acetate = 1) (based on Stoddard Solvent)
SOLUBILITY IN WATER:	Insoluble.
FLASH POINT:	148°F (64°C) (approximately) Tag Closed Cup
FLAMMABLE LIMITS IN AIR:	LOWER: 0.7 VOL% (minimum) UPPER: 5 VOL% (maximum)
AUTOIGNITION TEMPERATURE:	410°F (210°C) (minimum)

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.
INCOMPATIBILITY:	Avoid acids, alkalies, oxidizing agents, reducing agents, or reactive halogens.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

REACTIVITY: Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION PRODUCTS: None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

SECTION 11: TOXICOLOGICAL INFORMATION

SENSITIZATION: Based on best current information, there is no known human sensitization associated with these products.

MUTAGENICITY: Based on best current information, there is no known mutagenicity associated with these products.

CARCINOGENICITY: Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1, Group 2A, or Group 2B agents; or as listed by NTP as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

Also see **SECTION 15: CALIFORNIA.**

REPRODUCTIVE TOXICITY: Based on best current information, there is no known reproductive toxicity associated with these products.

Also see **SECTION 15: CALIFORNIA.**

TERATOGENICITY: Based on best current information, there is no known teratogenicity associated with these products.

TOXICOLOGICALLY SYNERGISTIC PRODUCT(S): Based on best current information, there are no known toxicologically synergistic products associated with these products.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: A Static Acute Bioassay as per the California Department of Fish and Game WPCL, was done using fathead minnows, and up to 750 ppm of the products in water.

The material passed the bioassay with only 1 out of 10 minnows dying. To fail the bioassay, more than 40% of the fish would die in 750 ppm.

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

OCTANOL/WATER

PARTITION COEFFICIENT: Not available.

VOLATILE ORGANIC COMPOUNDS: 100 WT%; 6.5 to 6.8 LB/US gal; 780 to 820 g/l
As per 40 CFR Part 51.100(s).

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding recycling or proper disposal.

USEPA WASTE CODE(S): Not regulated.
Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.

SECTION 14: TRANSPORT INFORMATION

DOT: COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM NAPHTHA),
NA1993, PG III

TDG: Not regulated.

EMERGENCY RESPONSE GUIDE NUMBER: 128
Reference *North American Emergency Response Guidebook*

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

SARA SECTIONS 302 AND 304: Based on the ingredient listed in **SECTION 2**, these products do not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA SECTIONS 311 AND 312: These products pose the following physical and health hazards as defined in 40 CFR Part 370 and are subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):
Immediate (Acute) Health Hazard
Delayed (Chronic) Health Hazard
Fire Hazard

SARA SECTION These products do not contain toxic chemicals subject to the

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

313: requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA: Based on the ingredient listed in **SECTION 2**, these products do not contain any "hazardous substance" listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

TSCA: All the components of these products are listed on the TSCA Inventory.

CALIFORNIA: These products may contain detectable amounts of benzene CAS 71-43-2 (at or below 0.4 mg/L) and p-dichlorobenzene CAS 106-46-7 (at or below 5 mg/L). **WARNING:** These chemicals are known to the State of California to cause cancer.

These products may contain detectable amounts of benzene CAS 71-43-2 (at or below 0.4 mg/L) and toluene CAS 108-88-3 (at or below 30 mg/L). **WARNING:** These chemicals are known to the State of California to cause birth defects or other reproductive harm.

CANADIAN REGULATIONS

These products have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS: B3, D2B

**CANADIAN
ENVIRONMENTAL
PROTECTION ACT
(CEPA):**

All the components of these products are listed on the Canadian Domestic Substances List (DSL).

**SAFETY-KLEEN PREMIUM SOLVENT
SAFETY-KLEEN PREMIUM GOLD SOLVENT
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

SECTION 16: OTHER INFORMATION

REVISION INFORMATION: Updated with Safety-Kleen Texas address, modified Medical Emergency phone number, modified Transportation Spill number and modified Technical Information phone number.

LABEL/OTHER INFORMATION: These products are United States Department of Agriculture (USDA) approved and Underwriter's Laboratories (UL) classified.

User assumes all risks incident to the use of these products. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the products as supplied to the user.



©2002 Printed in the USA.