

ITEM: 1UH88 - Marker White

MSDS: B1342

PICK REQ: 1082868858

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

SAFETY DATA SHEET - B1342

Associated Grainger Item: 1UH88 - Marker White

MATERIAL SAFETY DATA SHEET

SKM(TM)

SKM INDUSTRIES, INC

HMSL (R\*): HEALTH 2, FLAMMABILITY 3, REACTIVITY 0, PERSONAL PROTECTION B

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

IDENTITY: SUPER MET-AL MARKER (WHITE, NUCLEAR GRADE WHITE)
ITEM NO.: 04030, 04000, 1296-1295, 01295, 2000-3001, 03001, 03014, 2000-3010
FORMULA: SKM101

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

ANOTHER EXCLUSIVE PRODUCT OF: SKM INDUSTRIES, INC.

ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE): 1012 UNDERWOOD ROAD OLYPHANT, PA 18447

PRODUCT CLASS: SOLVENT BASED MARKER.

EMERGENCY TELEPHONE NUMBER: 800-424-9300 (CHEMTREC)

TELEPHONE NUMBER FOR INFORMATION: 570-383-3062

DATE PREPARED: 02/19/2007

SIGNATURE OF PREPARER (OPTIONAL): REGULATORY DEPT.

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

Table with 6 columns: HAZARDOUS COM (SE), CAS NO., OSHA PEL, ACGIH-TLV, OTHER LIMITS RECOMMENDED, % (OPT.). Rows include XYLENE, TITANIUM DIOXIDE, HYDROCARBON RESIN, ETHYL BENZENE, and HYDROCARBON RESIN.

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: WHITE OPAQUE THIN VISCOSITY LIQUID WITH AROMATIC ODOR.

WARNING!

FLAMMABLE LIQUID AND VAPOR. KEEP AWAY FROM HEAT SPARKS AND FLAMES. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. IF SWALLOWED DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

POTENTIAL HEALTH EFFECTS:

EYES: LIQUID IS MODERATELY IRRITATING TO THE EYES.

SKIN: LIQUID IS MILDLY IRRITATING TO THE SKIN.

INGESTION: INGESTION OF LIQUID MAY CAUSE VOMITING.

INHALATION:

HIGH CONCENTRATION OF VAPORS MAY PRODUCE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS, AND NAUSEA.

CHRONIC HEALTH EFFECTS:

PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN SENSITIZATION OR DERMATITIS. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH IRREVERSIBLE BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING OR INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL. IARC (INTERNATIONAL AGENCY FOR RESEARCH OF CANCER) HAS CLASSIFIED ETHYL BENZENE AS A POSSIBLE HUMAN CARCINOGEN (2B).

SECTION 4 FIRST AID MEASURES

EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: FLUSH SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES.

INGESTION: IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED): 79 F

FLAMMABLE LIMITS: LEL: 1.9, UEL: 12.3

EXTINGUISHING MEDIA: USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.

SPECIAL FIRE FIGHTING PROCEDURES: KEEP CONTAINERS COOL AND VAPORS DOWN WITH WATER SPRAY. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND, OR BE MOVED BY VENTILATION AND BE IGNITED BY IGNITION SOURCE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

SMALL SPILL: ABSORB LIQUID WITH NON-COMBUSTIBLE FLOOR ABSORBENT AND PLACE IN NON-LEAKING CONTAINER; SEAL PROPERLY AND DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

LARGE SPILL: EVACUATE AREA OF UNPROTECTED PERSONNEL. ELIMINATE ALL IGNITION SOURCES. STOP SPILL AT SOURCE IF SAFE TO DO SO.

HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY.

ABSORB UNRECOVERABLE PRODUCT. TRANSFER CONTAMINATED ABSORBENT, SOIL AND OTHER MATERIALS TO CONTAINERS FOR DISPOSAL. DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 7 HANDLING AND STORAGE

HANDLING: EMPTY CONTAINERS RETAIN RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, SPARKS, FLAMES, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. MANY HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR "IGNITION TEMPERATURES. IGNITION TEMPERATURES DECREASE WITH INCREASING VAPOR VOLUME AND VAPOR VOLUME AND VAPOR/AIR CONTACT TIME, AND ARE INFLUENCED BY PRESSURE CHANGES. IGNITION OF ORGANIC CHEMICAL VAPORS MAY OCCUR AT TYPICAL ELEVATED TEMPERATURE PROCESS CONDITIONS, ESPECIALLY IN PROCESSES OPERATING UNDER VACUUM IF SUBJECTED TO SUDDEN INGRESS OF AIR, OR OUTSIDE PROCESS EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS OR MISTS TO THE ATMOSPHERE OCCURS. ANY PROPOSED USE OF THIS PRODUCT IN ELEVATED TEMPERATURE PROCESSES SHOULD BE THOROUGHLY EVALUATED TO ASSURE THAT SAFE OPERATING CONDITIONS ARE ESTABLISHED AND MAINTAINED.

STORAGE: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. STORE IN COOL, WELL-VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIALS. INFORMATION ON THIS MATERIAL SAFETY DATA SHEETS REFERS TO INK USED IN PENS AND MARKERS, HOWEVER, IT APPLIES TO THESE INKS IN BULK. THE INKS ARE CONTAINED IN CAPILLARY OR VALVE RESERVOIRS AND WILL NOT SPILL OR LEAK UNDER NORMAL CONDITIONS.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT USUALLY NECESSARY. USE WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR IF PELS OR TLVS ARE EXCEEDED.

ENGINEERING CONTROLS: LOCAL EXHAUST: NOT USUALLY NEEDED, MECHANICAL (GENERAL): YES, SPECIAL: NONE, OTHER: NONE

PROTECTIVE GLOVES: CHEMICAL RESISTANT GLOVES IF SKIN CONTACT IS POSSIBLE (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER).

EYE PROTECTION: NOT NORMALLY REQUIRED IF USED AS INTENDED. WEAR CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATION IF SPLASHING IS POSSIBLE.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NOT USUALLY NECESSARY. FOR BULK MATERIAL, IF DIRECT CONTACT IS POSSIBLE, WEAR APRON, BOOTS, FACE SHIELD, ETC. AS NEEDED.

WORK/HYGIENIC PRACTICES:  
FOLLOW LABEL INSTRUCTIONS. WASH HANDS AFTER USE AND BEFORE EATING, DRINKING,  
SMOKING, USING RESTROOMS, ETC.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 282 TO 286 DEG. F

VAPOR PRESSURE (MM-Hg @ 70 DEG. F): NO DATA

VAPOR DENSITY (AIR = 1): GREATER THAN ONE (1)

SOLUBILITY IN WATER: NEGLIGIBLE

SPECIFIC GRAVITY (H2O = 1):  
@70 DEG. F: >1

MELTING POINT: NO DATA

EVAPORATION RATE (BUTYL ACETATE = 1): LESS THAN ONE (1)

pH: NO DATA

APPEARANCE AND ODOR: WHITE OPAQUE THIN VISCOSITY LIQUID WITH AROMATIC ODOR.

SECTION 10 STABILITY AND REACTIVITY

CHEMICAL STABILITY:

UNSTABLE ( )  
STABLE (X)

CONDITIONS TO AVOID: NONE KNOWN.

INCOMPATIBILITY (MATERIALS TO AVOID):  
STRONG OXIDIZING AND REDUCING AGENTS, STRONG ALKALIES AND STRONG ACIDS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:  
CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, SOOT AND VARIOUS ORGANIC OXIDATION  
BY-PRODUCTS.

HAZARDOUS POLYMERIZATION:  
MAY OCCUR ( )  
WILL NOT OCCUR (X)

CONDITIONS TO AVOID: NO DATA

SECTION 11 TOXICOLOGICAL INFORMATION

ORAL LD50 (RAT) DERMAL LD50 (RABBIT) INHALATION LC50 (RAT)

XYLENE 4300 MG/KG NO DATA NO DATA

HYDROCARBON >500 MG/KG NO DATA NO DATA  
RESIN

PLEASE REFER TO SECTION 3 FOR AVAILABLE INFORMATION ON POTENTIAL HEALTH  
EFFECTS.

SECTION 12 ECOLOGICAL INFORMATION

NO SPECIFIC ECOLOGICAL DATA ARE AVAILABLE FOR THIS PRODUCT. PLEASE REFER TO  
SECTION 6 FOR INFORMATION REGARDING ACCIDENTAL RELEASES AND SECTION 15 FOR  
REGULATORY REPORTING INFORMATION.

SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL  
REGULATIONS.

SECTION 14 TRANSPORT INFORMATION

(NOT MEANT TO BE ALL INCLUSIVE):

DOMESTIC HIGHWAY (CONTAINERS <1 QUART ARE ORM-D):

PROPER SHIPPING NAME: PAINT

HAZARD CLASS/SUBSIDIARY HAZARD: 3

UN/NA NO.: UN1263

PACKING GROUP: II

LABEL REQUIRED: FLAMMABLE LIQUID (3)

DOMESTIC AIR SHIPMENTS (PENS):

PROPER SHIPPING NAME: CONSUMER COMMODITY

HAZARD CLASS/SUBSIDIARY HAZARD: 9

UN/NA NO.: I.D. 8000

PACKING GROUP: NONE

LABEL REQUIRED: CLASS 9

SECTION 15 REGULATORY INFORMATION

(NOT MEANT TO BE ALL INCLUSIVE - SELECTED REGULATIONS REPRESENTED):

U.S. FEDERAL REGULATIONS:

CARCINOGENICITY:

NIH ( )  
IA ( ) NOGRAPHS?: 2B  
OS ( ) REGULATED?: NO

OSHA:  
HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

SECTION 313:  
THIS PRODUCT CONTAINS XYLENE (1330-20-7) AND ETHYL BENZENE (100-41-4) WHICH

ARE LISTED AND MAY REQUIRE REPORTING UNDER SARA TITLE III SEC. 313 IF USED  
OVER THE THRESHOLD REPORTING QUANTITY. THIS INFORMATION MUST BE INCLUDED IN  
ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS: NOT WHMIS CONTROLLED (PENS)  
BULK: CLASS B2, D2A

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:  
THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY MATERIAL LISTED UNDER CALIFORNIA'S  
PROPOSITION 65.

SECTION 16 OTHER INFORMATION

MSDS STATUS:

REVISED SECTION(S):

WARNING!

THE USE OF THIS PRODUCT IS BEYOND THE CONTROL OF THE MANUFACTURER AND  
DISTRIBUTOR; THEREFORE, NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE AS TO  
THE EFFECTS OF SUCH OR THE RESULTS TO BE OBTAINED IF NOT USED IN ACCORDANCE  
WITH DIRECTIONS OR ESTABLISHED SAFE PRACTICE. THE USER MUST ASSUME ALL  
RESPONSIBILITY, INCLUDING INJURY OR DAMAGE, RESULTING FROM ITS MISUSE AS  
SUCH, OR IN COMBINATION WITH OTHER MATERIALS. THE MANUFACTURER AND  
DISTRIBUTOR WARRANT ONLY THAT THIS PRODUCT MEETS THE SPECIFICATIONS FOR SUCH  
PRODUCT.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO  
DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE,  
PRODUCTIVENESS, OR ANY OTHER MATTER OF THIS PRODUCT. THE MANUFACTURER AND  
DISTRIBUTOR SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS  
PRODUCT. THE SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER AND  
DISTRIBUTOR FOR BREACH OF WARRANTY SHALL BE REIMBURSEMENT OF THE PURCHASE  
PRICE OF THE PRODUCT IN THE EVENT THAT A DEFECTIVE CONDITION OF THE PRODUCT  
SHALL BE FOUND TO EXIST. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO  
INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY  
OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.

ORDER: 1082868858

ITEM: 1UH88 - Marker White

HAZMAT: 1UH88

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit.

GRAINGER SHIPPING INFORMATION

STOCK # : 1UH88  
 MSDS # : B1342  
 FREIGHT CODE : 0897  
 DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT 26 DGS C, 79 DGS F

FLASHPOINT : 26 DEGREES CELSIUS, 79 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D  
 UN ID # :  
 PACKING GROUP :  
 SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES  
 CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON  
 DOT/UPS EXEMPTION NO. :  
 COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!  
 SHIPPING-PAPERS :

CARD OFFERED ? YES ( ) NO ( ) PLEASE MARK ONE

\*\*\*\*\*